



LED display for indoor/outdoor for n° 6 photovoltaic plant parameter (Current Power, Energy Day, Field Irradiation, Total Energy, Last year Energy, avoided CO<sub>2</sub>), RS485 communication, amber LED.

With customizable graphics, anti-glare screen, automatic brightness control via light sensor, visibility up to 50 meters. B. 2400 x 1350 x H. P. 75 mm dimensions , 120 mm character height, 28kg weight. Completed with brackets for wall mounting.

## TECHNICAL SPECIFICATIONS

<b>Weight</b>	28 kG
<b>Dimensions</b>	B. 2400 x H. 1350 x P. 75 mm
<b>Led written height</b>	120 mm
<b>Text Size</b>	75 mm x 120 mm
<b>Total visible area</b>	4320 x 120 mm
<b>MAX visibility</b>	50 mt
<b>Front screen</b>	Anti-glare screen
<b>Colors quantity</b>	1 (amber)
<b>Mechanics Model</b>	F Model / 2006 Cover
<b>Display fixing</b>	Brackets for wall mounting
<b>Custom graphics version</b>	On request can print an image wide-ranging
<b>Display structure</b>	Entirely in aluminum
<b>Screws / Fixings</b>	steel
<b>Type of protection</b>	Interior / exterior
<b>Pixel</b>	1 Led high brightness
<b>Pixel N°</b>	1920
<b>Rate</b>	15 mm
<b>Lines N°</b>	6
<b>Characters N° per line</b>	8
<b>Display Characters N°</b>	48 in all
<b>Brightness control</b>	Automatically by light sensor
<b>Communication</b>	RS485
<b>Power supply</b>	220 V - 50Hz

## ORDERING CODE

**SIN.EXTTLED6**